

### Overview



### Model

HP Presentation Barcode Scanner

Part Number: QY439AA

### Introduction

The HP Presentation Barcode Scanner is a sleek POS solution that features a user-friendly design, small footprint, and efficient capture of a wide range of 1D and 2D barcodes, including barcodes presented on mobile devices, all at a competitive price point. This all-new general purpose on-counter presentation scanner can be mounted to most surfaces and delivers automatic movement recognition and hand-free operation.

### Key Features and Benefits

- Reads most common 1D and 2D barcodes, PDF codes and GS1 DataBar for a range of flexible uses.
- Omni-directional operation allows symbol or image capture regardless of the orientation of the scanner for quicker reading.
- Enhanced motion tolerance and technology allow quick reading of barcodes from mobile devices.
- Intuitive feedback following a successful read indicated by a sound and shown by a visual green light shown on the device.
- Scanner is able to read poorly printed or damaged barcodes successfully for quicker checkout.
- Fixed mounting plate allows the scanner to be mounted to most surfaces to help decrease the likelihood of being dropped or knocked over a counter.

### Compatibility

The HP Presentation Barcode Scanner is compatible with HP Retail Point of Sale Systems.

**NOTE:** Not all Point of Sale system models are available in all regions.

### Service and Support

Your HP Peripheral Limited Warranty is a three (3) year (HP Option Limited Warranty Period) parts replacement warranty.



### Technical Specifications

#### General

Scanner type	Imager
Light source	LEDs
Nominal working distance	Depth of Field Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

#### 1D Linear Codes

- 5 mils: 0 to 2.5 cm / 0 to 1.0 in
- 7.5 mils: 0 to 8.2 cm / 0 to 3.25 in
- 10 mils: 0 to 12.7 cm / 0 to 5.0 in
- 13 mils UPC: 0 to 15.2 cm / 0 to 6.0 in

#### 2D Linear Codes

- 6.6 mils PDF: 3.8 to 7.6 cm / 0 to 3.0 in
- 10 mils Data Matrix: 0.64 to 3.1 cm / 0.25 to 1.25 in
- 10 mils PDF: 0 to 12.7 cm / 0 to 5.0 in
- 15 mils PDF: 0 to 15.2 cm / 0.0 to 6.0 in
- 24 mils Data Matrix: 0 to 12.7 cm / 0 to 5.0 in

Print contrast	25% minimum reflectance
Roll (tilt)	± 0-360°
Pitch	± 60°
Skew	± 60°
1D/2D decode symbologies	<u>Factory Default Barcodes*</u>  CODE 39 CODE 93 CODE 128 DataMatrix EAN-8 EAN-13 GS1 DataBar Expanded GS1 Databar Omni-directional PDF417 UPC-A UPC-E

\*HP factory setting has these code selections enabled by default.

#### Mechanical

Dimensions (W x D x H)	3 x 6 x 4 in (.76 x 1.52 x 1.01 cm)
Weight	Approximately 10 ounces (295 g)
Cable length	6.5 ft (1.9 m)
Color	Black



### Technical Specifications

#### Interface/Connection

Cable	USB
-------	-----

#### Temperature

Operating	32 to 104 °F (0 to 40 °C)
Storage/transport	-40 to 158 °F (-40 to 70 °C)
Humidity (non-condensing)	5 - 95%

#### Power

Voltage & current	Input Current at 5V = <350 mA (max) Idle Current at 5V = <250 mA (max)
-------------------	---

#### Drivers

Windows UBB HID-KB and OPOS & JPOS (via USB-COM mode drivers)

#### Operating System

Compatible with:	Genuine Windows Vista® Business 32 Genuine Windows XP Professional Genuine Windows Embedded for Point of Service (WEPOS) Genuine Windows Embedded POSReady 2009 Genuine Windows Embedded POSReady 7 32 bit Genuine Windows Embedded POSReady 7 64 bit Genuine Windows 7 Business 32 Genuine Windows 7 Business 64
------------------	--

#### Agency Certifications

C-Tick, VCCI, CSA, CE, FCC

#### Option Kit Contents

HP Presentation Barcode Scanner, USB Cable, HP Point of Sale System Software and Documentation CD.

---

© Copyright 2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

